

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 December 2001 (13.12.2001)

PCT

(10) International Publication Number
WO 01/93781 A2

(51) International Patent Classification⁷: A61F 2/06

(21) International Application Number: PCT/US01/18419

(22) International Filing Date: 5 June 2001 (05.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/209,255 5 June 2000 (05.06.2000) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 60/209,255 (CIP)
Filed on 5 June 2000 (05.06.2000)

(71) Applicant and

(72) Inventor: JANG, G., David [US/US]; 30725 Eastern Lane, Redlands, CA 92374 (US).

(74) Agent: DAVIS, Paul; Wilson Sonsini Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: INTRAVASCULAR STENT WITH INCREASING COATING RETAINING CAPACITY

(57) Abstract: An expandable stent includes a tubular structure with an outer surface positionable adjacent to a vessel wall and an inner surface facing a lumen of a body passageway. The tubular structure further includes a plurality of expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter which is achieved upon the application of a radially, outwardly extending force. A plurality of cavities are formed in the outer surface of the stent.

WO 01/93781 A2

INTRAVASCULAR STENT WITH INCREASING COATING
RETAINING CAPACITY

5 BACKGROUND OF THE INVENTION

Field of Invention:

10 This invention relates generally to intravascular stents, and more particularly to intravascular stents that include a plurality of cavities formed on a surface of the stent and are coated with a restenosis inhibiting agent.

Description of the Related Art:

15 By 1999, the percutaneous balloon angioplasty and stent implant procedures have become the dominant non-surgical revascularization method of the atherosclerotic stenosis, or obstruction, of the vascular lumen, and particularly in the coronary vascular system in the heart. With balloon angioplasty alone, without use of stent, the restenosis rate after angioplasty has
20 been as high as 25-45% in the first time clinical cases. With use of stents after balloon angioplasty, the restenosis has been reduced significantly. Even so, the restenosis rate after stent implant is reported as 10-25% range depending on the condition of the vessel stented or what specific stent was used, requiring a need for further restenosis reducing measures after intravascular stenting.

25 To further reduce the restenosis rate after stent implant, numerous means has been tried, including laser, atherectomy, high frequency ultrasound, radiation device, local drug delivery, etc. Although the brachytherapy (radiation treatment) has proved to be reasonably effective in further reducing restenosis after stent implant, using brachytherapy is very cumbersome,
30 inconvenient and costly. Mainly because it is radioactive device and radiation therapy specialist from another department has to be involved with the interventional cardiologist in the cardiac catheterization laboratory. The laser

and atherectomy devices proved to be marginally useful in this purpose with added costs.

5 The local drug therapy appears be a very promising method for the future, as better pharmaceutical, chemical or biogenetic agents are developed and became available. Some research data, both from animal tests and human clinical studies, indicate that there are evidences of suppressing restenosis after stent implant when certain growth blocking pharmaceutical agents available today are used to coat the stent. In another instances, it has been speculated that
10 certain surface modifying materials coated on the surface of the stent may be beneficial by it alone or in combination with growth suppressing agent, in reducing restenosis rate. In either instance, the drug or substance should be locally attached or coated on the stent and in sufficient amounts. However, attaching or coating a sufficient amount of a substance or drug on the coronary
15 stent is not so easy a proposition.

Coating a drug or an agent on the surface of the stent has a demanding problem of enough volume of such substance coated on the small surface areas of stent struts, without increasing the physical width or thickness of stent struts. This demand directly conflicts with the metal fraction issue of the stent. If the
20 width (and lesser degree the thickness) of stent struts is increased in order to widen drug coating surface areas, it would have an elevated deleterious foreign body effect of the increased metal fraction of the stent, which would promote restenosis.

Designing an ideal stent, particularly the coronary stent, is a very
25 demanding balance of a numerous conflicting factors. An ideal stent requires an ideal balance of numerous different stent features built into the stent. One of the many requirements of a coronary, or any vascular stent, is to keep the metal fraction of the stent low. This means that drug coating is a very demanding task. Enough amounts of a drug or agent should be coated on the miniscule
30 surface areas of the stent struts, in order to have the desired drug results of reducing restenosis. An average stent, particularly a coronary stent, will have problem of providing desired amount of drug-retaining capacity on the surface areas of the stent struts.

The main invention of this application is not an invention of the stent itself. The present invention is the particular measures designed to increase drug coating or attachment capacity of a stent by adding exposed surface areas or reservoir capacity of the stent, without increasing the width or thickness of the stent struts or without increasing the metal fraction of the stent. These special measures of present invention will enhance the coating substances to a stent. Further, the present invention will enhance the reservoir capacity of the stent for different forms of restenosis reducing proteins, chemicals or drugs, and will prolong the releasing time duration of the substances.

U.S. Patent No. 6,190,404 discloses an intravascular stent with an outer surface, an inner surface and grooves formed in the inner surface of the stent. The grooves are positioned and provided to increase the rate of migration of endothelial cells upon the inner surface of the stent.

There is a need for a stent with a geometry that provides for an increased amount of a coating substance. There is a further need for a stent that includes reservoirs for retaining coatings.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide an intravascular stent with a geometry that provides for an increased amount of a coating substance.

Another object of the present invention is to provide an intravascular stent with cavities formed in the stent that serve as reservoirs of coatings applied to the stent.

Yet another object of the present invention is to provide an intravascular stent with cavities formed in the body of the stent and with a restenosis inhibiting agent applied to the stent.

Another object of the present invention is to provide an intravascular stent with micro-holes or micro-slits that provide reservoirs for stent coatings.

These and other objects of the present invention are achieved in an expandable stent. A tubular structure includes an outer surface positionable adjacent to a vessel wall and an inner surface facing a lumen of a body

passageway. The tubular structure further includes a plurality of expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter which is achieved upon the application of a radially, outwardly extending force. A plurality of cavities are formed in the outer surface of the stent.

In another embodiment of the present invention, an expandable stent, includes a tubular structure with an outer surface positionable adjacent to a vessel wall, an inner surface facing a lumen of a body passageway, a plurality of expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter that is achieved upon the application of a radially, outwardly extending force. A plurality of cavities formed in the outer surface of the stent. A coating substance is on at least a portion of outer surface of the stent including and extends into at least a portion of the cavities.

In another embodiment of the present invention, a stent assembly includes a balloon and an expandable stent positioned at an exterior of the balloon. The stent includes a tubular structure with an outer surface positionable adjacent to a vessel wall, an inner surface facing a lumen of a body passageway, a plurality of expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter that is achieved upon the application of a radially, outwardly extending force applied by the balloon. A plurality of cavities are formed in the outer surface of the stent. A coating substance is on at least a portion of outer surface of the stent including and extending into at least a portion of the cavities.

In another embodiment of the present invention, a method of manufacturing an intravascular stent is provided. The intravascular stent has an inner surface and an outer surface. A plurality of cavities are formed on the outer surface. A coating substance that inhibits restenosis is formed on at least a portion of the outer surface and on at least a portion of the plurality of cavities

BRIEF DESCRIPTION OF DRAWINGS

5 Figure 1 is a flat cut-open, two-dimensional, schematic view of one embodiment of a stent of the present invention that includes cavities formed in the body of the stent.

Figure 2 is a close-up view of the stent from Figure 1 with cavities that extend from the outer surface of the stent into an interior of the stent.

10 Figure 3 is a cross-section, side view of a stent of the present invention with cavities that extend from the outer surface through the inner surface.

Figure 3(b) is a cross-sectional, magnified, side view of one embodiment of the stent of the present invention illustrating that cavities can be closed and serve as reservoirs for coating substance applied to the stent.

15 Figure 3(c) is a cross-sectional, magnified view of another embodiment of the present invention illustrating a stent that includes cavities that extend at a slant angle from the outer surface through the inner surface.

Figure 3(d) is a cross-sectional, magnified, side view of one embodiment of the present invention with cavities that extend at a slant, non-perpendicular angle from the outer surface to an interior of the stent.

20 Figure 4 is a flat cut-open, two-dimensional, schematic view of a stent seen from the outer surface of the stent cavities distributed in an even pattern

Figure 5 is a close-up, magnified, view of the expansion and connector struts from Figure 4 with micro-slits and micro-holes that extend from the outer surface of the stent struts.

25 Figure 6(a) is a cross-sectional, magnified, side view of a stent strut of the present invention illustrating micro slits that extend through both the outer and inner surfaces and the entire thickness of the stent strut.

30 Figure 6(b) is a cross-sectional, magnified, side view of the stent strut of the present invention illustrating perpendicularly extending open micro slits on one side and closed micro-slits on the opposite site of the strut.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to Figure 1, one embodiment of an expandable stent 10 of the present invention is illustrated. A tubular structure includes an outer surface positionable adjacent to a vessel wall and an inner surface facing a lumen of a body passageway. The tubular structure further includes a plurality of
5 expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter which is achieved upon the application of a radially, outwardly extending force.

A plurality of cavities are formed in the outer surface of the stent. The
10 cavities can be micro-holes or micro-slits and extend from the outer surface to an interior of the struts, or extend from the outer surface all the way through the inner surface. An example of a stent design useful with the present invention is disclosed in US Patent 5,954,743, incorporated herein by reference. In Figure-1, a two-dimensional view of the stent 10 is illustrated and is seen from the
15 outer surface of the cut-open, two-dimensional view.

Stent 10 includes expansion columns 12 and connector columns 14 in a continuous and alternating pattern to form a longitudinal dimension and a vertical dimension. The vertical and longitudinal dimensions determine the circumference and the length respectively of stent 10. Expansion columns 12
20 have expansion struts 16 in a vertical zigzag or corrugated pattern. One expansion column 12 is linked to an adjacent expansion column 12 by connector column 14 between two adjacent expansion 12 columns. Connector columns 14 have connector struts 18 that serve as linking arms between expansion struts 16 in two adjacent expansion columns 12. Stent 10 has a
25 proximal end 20 and a truncated end 22 in the middle of stent 10.

In one embodiment, stent 10 is a tubular structure that includes patterned expansion struts 16 and connectors struts 18 continuously linked circumferentially and longitudinally with a predetermined length. The total surface areas of struts 16 and 18 are limited to a certain percent of the total
30 cylindrical surface area of tubular stent 10, particularly when stent 10 is expanded in a vessel, with enlarged (by stent expansion) stent cells 24 that make up the remainder of the total stent surface area.

The amount of a coating substance applied to and retained by stent 10 is determined by the total surface area of stent struts 16 and 18. Coating substance is preferably a restenosis inhibiting agent that is a drug, polymer and bio-engineered material and combinations thereof. It will be appreciated that other types of coating substances, well known to those skilled in the art, can be applied to stent 10 of the present invention. Because the total stent strut surface areas are limited in size, the amount of coating substance applied to stent 10 is limited to a small volume. When stent 10 is expanded in a vessel the relative surface area of struts 16 and 18 decreases in relation to the areas of stent cells 24. The total cylindrical surface area of stent 10 when it is implanted and expanded inside of a vessel is equal to the sum of the strut surface areas, which do not change, and stent cells 24 areas. The size of stent cells 24 areas changes when stent 10 is expanded. The present invention increases the amount of the coating substance capacity of stent 10 without increase the metal fraction of stent 10.

In various embodiments, the present invention increases the coating substance retaining capacity of stent 10 by forming cavities that can be micro holes 26 which are made, punched, drilled or burned into the expansion and connector struts 16. In Figure 1, micro holes 26 have openings 28 on outer surface of struts 16 and 18. Micro holes 26 are made and arranged in such a way so that they can be evenly distributed in struts 16 and 18. In this embodiment, micro holes 26 are evenly distributed through out the entire body of stent 10. The number of micro holes 26 illustrated in Figure-1 is only by example.

The number of micro holes 26 created in stent 10 can vary by increasing or decreasing the number according to the necessity and requirements when such stents are fabricated for clinical use. Additionally, the pattern of creating micro holes 26 in stent struts 16 and 18 can be varied according to the clinical and protocol needs. Although micro holes 26 in Figure 1 are made in straight lines it will be appreciated that micro holes 26 can be made in any varied pattern or shape. Micro-holes 26 can be made to form any suitable shape or pattern as necessary, if they meet the structural or engineering requirements of

stent 10. Micro holes 26 can be made in single line or in multiple lines in struts 16 and 18 and arranged in any pattern.

In the embodiment illustrated in Figure 2, width 30 of expansion strut 16 is shown as being larger than width 32 of connector strut 18. It will be appreciated that the relative widths can change and that width 32 can be greater than width 30.

The size of micro holes 26 can be based on the physical dimensions of struts 16 and 18. Micro holes 26 cannot have diameters or size as large as the width of struts 16 and 18. Micro holes 26 can have substantially smaller widths or diameters than widths 30 and 32 in order to maintain the structural integrity and radial strength of stent 10. In one embodiment, micro holes 26 have an effective size or diameter to provide an optimal retaining capacity of substances or drugs that are coated or deposited on stent 10. Similarly, the distance between micro holes 26 is selected to maintain the integrity of stent 10 while providing an optimal number of micro holes 26 to provide a sufficient coating substance retaining capacity. Micro holes 26 in struts 18 can be made smaller than micro holes 26 in expansion struts 16 and visa versa.

Micro holes 26 and opening 28 can have more than one shape including but not limited to circular, square, oval, oblong, irregular, polygonal or a combination thereof, depending on the method used to create micro holes 26. The tools to create micro holes 26 can be mechanical, photochemical, laser, EDM and the like.. The shape or configuration of micro holes 26 and openings 28 in stent struts 16 and 18 can be influenced by the size or diameter of the micro hole 26 made, as well as by other manufacturing factors such as a laser beam size, photochemical resolution or EDM cathode and the like.

In the embodiment of Figure 3(a), micro holes 26 penetrate the entire widths 30 and 32 of struts 16 and 18 at a perpendicular angle with opening 28 on both outer surface 34 and inner surface 36. Shaded areas 38 show the cross-sectional cut surface of struts 16 and 18. Micro holes 26 are created in a regular interval with the uninterrupted segment 28 between micro holes 26. Micro holes 26 communicate freely between outer surface 34 and inner surface 36. As can be seen, micro holes 26 increase the contact surface areas of stent struts 16 or 18 for the purpose of increasing the capacity of retaining the intended coating

substance added to stent 10. The bore space of micro holes 26 also serve as micro reservoir chambers for the substance to be added, attached or coated to stent 10. When stent 10 is electropolished, the shape or dimension of micro holes 26 can be slightly changed.

5 Figure 3(b) illustrates an embodiment where micro holes 36 are blind and extend from outer surface 34 but not do not continue to inner surface 36. Shaded areas 38 indicate cross-sectioned stent struts 16 and 18. In Figure 3(b), micro holes 26 have cul de sac geometry's 40 that terminate in an interior of struts 16 and 18. Cul-de-sacs 40 serve as reservoirs for coating substances
10 applied to stent 10. Cul-de-sacs 40 can be created at regular or irregular intervals with uninterrupted segments 42 between that are formed between micro holes 26.

Referring now to Figure 3(c), micro holes 26 are shown with their axes at a slant angle relative to stent struts 16 and 18. In this embodiment, micro
15 holes 26 extend from outer surface 34 to inner surface 36. Because micro holes 26 have a slant angle through in this embodiment, the length and reservoir capacity of the micro holes 26 is increased compared to the capacity of the Figure 3(a) micro holes 26.

In the embodiment illustrated in Figure 3(d), micro holes 26 have
20 openings 28 on outer surface 34 and cul de sacs 40 on inner surface 36, all formed at a slant angle. Outer surface 34 has uninterrupted segments 42 between slant angled micro holes 26 and inner surface 36 is smooth without openings 28. Again, cul-de-sac 40 provides a reservoir for a coating substance applied to stent 10. Because the bore space of micro holes is at a slant angle
25 there is an increased reservoir capacity.

In contrast to Figure 1, the cavities formed in Figure 4 are micro slits, groves, and the like, collectively denoted as 40, which have widths 44 that are larger than openings 36. Compared to micro holes 26 of Figure 1, the micro
30 slits 40 shown in Figure 4 provide a larger reservoir capacity for the coating substance.

Micro slits 40 can be evenly or unevenly distributed in struts 16 and 18.. The number of micro slits 40 illustrated in Figure-4 is only by way of example. Increasing or decreasing the number of micro slits 40 created in stent 10 may

vary according to the clinical and pharmacodynamic necessity and requirements. Additionally, the pattern of creating micro slits 40 in struts 16 and 18 can vary according to the clinical and engineering needs. Although micro slits 40 illustrated in Figure-4 are in straight lines, micro slits 40 can be made in
5 curvilinear, square-angles, slant angled and the like with or without radius of curvature. Micro slits 40 can be made in any suitable pattern or shape as required, if they meet the structural or engineering requirements of stent 10. Micro slits 40 can be made in single line or in multiple lines in struts 16 and 18 and arranged in any other pattern. The Figure-4 embodiment illustrates that
10 micro holes 26 can also be included in the same stent 10.

The magnified view of stent 10 illustrated in Figure 5 shows struts 16 and 18 with micro slits 40 and openings 46 on outer surface 34 of stent 10. Width 34 of expansion strut 16 is larger than width 32 of strut 18 in this embodiment. However, widths 34 and 32 can be the same in size or even
15 reversed.

Width 44 of micro slit 40 is determined by the physical dimensions and limits of struts 16 and 18. Width 44 can not be made as large as widths 34 and 32. Width 44 is substantially smaller than width 34 in order to maintain the structural integrity and radial strength of stent 10. The length of micro slit 40
20 can be made as long as stent struts 16 and 18. The length of micro slit 40 can be shorter or longer than the width of struts 16 and 18. Similarly, the uninterrupted distance 42 between micro slits 40 is selected so that the structural integrity of stent 10 is not compromised. Within the allowable limits, micro slits 40 can be made in different sizes or dimensions in same or differing patterns. Micro slits
25 40 in struts 18 can be made smaller than, the same as or greater than micro-slits 40 formed in struts 16.

The shape of micro slits 40 and opening 46 can be different than that illustrated in Figure 5. The geometry of micro slits 40 can be straight linear, curvilinear, angled, squared or any other shape, depending on the design of stent
30 10 and the method used to make micro slits 40 during the manufacturing process. The tools to create the micro slits 40 can be the same as those used for micro-holes 26. Different shapes, sizes and positions of micro slits 40 can be included in an individual stent 10.

Referring now to Figure 6(a), micro slits 40 can extend through struts 16 and 18 with openings 50 on both outer and inner surfaces 34 and 36. Micro slits 40 can be created in a regular interval with uninterrupted segment 42 between micro slits 40.

5 Additionally, in this embodiment micro slits 40 can communicate freely between outer surface 34 inner surface 36. Micro slits 40 increase coating substance contact surface areas of struts 16 and 18 for the purpose of increasing the reservoir capacity of intended coating substances.

10 Figure-6(b) illustrates that blind micro slits 40 partially extend into struts 16 and 18 from outer surface 34. Blind micro slits 40 end in cul-de-sacs 48 which can be of any desired geometric configuration. Cul-de-sacs 48 create micro reservoirs 50 for coating substances and can be formed at regular or irregular intervals with uninterrupted segments 42 between blind micro slits 48. Generally, the reservoir capacity of blind micro slits 40 is greater than that of
15 blind micro holes 26. Additionally, Micro slits 40 can also be made in slant angles.

 The foregoing description of a preferred embodiment of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms
20 disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in this art. It is intended that the scope of the invention be defined by the following claims and their equivalents.

 What is claimed is:

CLAIMS

WHAT IS CLAIMED IS:

1. An expandable stent, comprising:
a tubular structure including an outer surface positionable adjacent to a
5 vessel wall, an inner surface facing a lumen of a body passageway, a plurality of
expansion struts, connector struts and cells, the tubular structure having a first
diameter which permits intraluminal delivery of the tubular structure into the
body passageway having a lumen, and a second expanded and deformed
10 diameter upon the application from the interior of the tubular member of a
radially, outwardly extending force; and
a plurality of cavities formed in the outer surface of the stent.
2. The stent of claim 1, wherein the tubular structure is balloon
expandable.
3. The stent of claim 1, wherein the tubular structure is self-
15 expandable.
4. The stent of claim 1, wherein at least a portion of the tubular
structure is made of a shape memory alloy.
5. The stent of claim 1, wherein the plurality of cavities are
substantially evenly positioned on the tubular structure.
- 20 6. The stent of claim 1 wherein the plurality of cavities increase a
flexibility of the stent without substantially reducing a radial strength of the
stent in a deployed state.
7. The stent of claim 1, wherein the plurality of cavities are micro-
holes that extend from the outer surface.
- 25 8. The stent of claim 7, wherein the micro-holes have a cross-
section that is smaller than a cross section of a strut.

9. The stent of claim 7, wherein the micro-holes extend from the outer surface through the inner surface.

10. The stent of claim 7, wherein the micro-holes extend from the outer surface to an interior of the tubular structure without extending through the inner surface.

11. The stent of claim 7, wherein at least a portion of the micro-holes extend from the outer surface through the inner surface and at least a portion extend from the outer surface to an interior of the tubular structure without extending through the inner surface.

12. The stent of claim 7, wherein at least a portion of the micro-holes have geometry's that are configured to provide a reservoir for a coating substance applied to the tubular structure.

13. The stent of claim 7, wherein at least a portion of the micro-holes have a diameter of at least 0.0007 inch.

14. The stent of claim 7, wherein at least a portion of the micro-holes extend perpendicular from the outer surface to an interior of the tubular structure.

15. The stent of claim 7, wherein at least a portion of the micro-holes extend at a non-perpendicular slant angle from the outer surface to an interior of the tubular structure.

16. The stent of claim 1, wherein the plurality of cavities are micro-slits that extend from the outer surface.

17. The stent of claim 16, wherein the micro-slits have a cross-section that is smaller than a cross section of a strut.

18. The stent of claim 16, wherein the micro-slits extend from the outer surface through the inner surface.

19. The stent of claim 16, wherein the micro-slits extend from the outer surface to an interior of the tubular structure without extending through the inner surface.

5 20. The stent of claim 16, wherein at least a portion of the micro-slits extend from the outer surface through the inner surface and at least a portion extend from the outer surface to an interior of the tubular structure without extending through the inner surface

10 21. The stent of claim 16, wherein at least a portion of the micro-slits have geometry's that are configured to provide a reservoir for a coating substance applied to the tubular structure.

22. The stent of claim 16, wherein at least a portion of the micro-slits have a width of at least 0.0007 inch.

23. The stent of claim 16, wherein at least a portion of the micro slits have a width greater than 0.0007 inch.

15 24. The stent of claim 16, wherein at least a portion of the micro slits have a length of at least .001 inch.

25. The stent of claim 16, wherein at least a portion of the micro slits have a length greater than .001 inch.

20 26. The stent of claim 16, wherein at least a portion of the micro-slits extend perpendicular from the outer surface to an interior of the tubular structure.

27. The stent of claim 16, wherein at least a portion of the micro-slits extend at a non-perpendicular slant angle from the outer surface to an interior of the tubular structure.

25 28. The stent of claim 16, wherein at least a portion of the micro-slits have a linear geometric shape.

29. The stent of claim 16, wherein at least a portion of the micro-slits have a curved geometric shape.

30. The stent of claim 16, wherein at least a portion of the micro-slits have a bottom surface formed in an interior of the tubular structure.

5 31. The stent of claim 30, further including at least one aperture that extends from the bottom surface of a micro-slit through the inner surface.

32. The stent of claim 30, further including a plurality of apertures that extend from the bottom surface of the micro-slit through the inner surface.

10 33. The stent of claim 1, further comprising:
a coating substance on at least a portion of outer surface of the stent including at least a portion of the plurality of cavities.

34. The stent of claim 33, wherein the coating substance is a restenosis inhibiting agent.

15 35. The stent of claim 34, wherein the restenosis inhibiting agent is selected from a drug, polymer and bio-engineered material.

36. The stent of claim 34, wherein the restenosis inhibiting agent is a combination of two agents selected from a drug, polymer and bio-engineered material.

20 37. The stent of claim 34, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to increase an amount of restenosis inhibiting agent coated on the stent.

38. The stent of claim 33, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to provide reservoir of the coated substance on the stent.

25 39. An expandable stent, comprising:
a tubular structure including an outer surface positionable adjacent to a vessel wall, an inner surface facing a lumen of a body passageway, a plurality of

expansion struts, connector struts and cells, the tubular structure having a first diameter which permits intraluminal delivery of the tubular structure into the body passageway having a lumen, and a second expanded and deformed diameter upon the application from the interior of the tubular member of a
5 radially, outwardly extending force;

a plurality of cavities formed in the outer surface of the stent; and

a coating substance on at least a portion of outer surface of the stent including and extending into at least a portion of the cavities.

40. The stent of claim 39, wherein the coating substance is on at
10 least a portion of the inner surface of the stent.

41. The stent of claim 39, wherein the coating substance is a restenosis inhibiting agent.

42. The stent of claim 41, wherein the restenosis inhibiting agent is selected from a drug, polymer and bio-engineered material.

43. The stent of claim 34, wherein the restenosis inhibiting agent is a
15 combination of two agents selected from a drug, polymer and bio-engineered material.

44. The stent of claim 40, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to increase an amount of
20 restenosis inhibiting agent coated on the stent.

45. The stent of claim 39, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to provide a reservoir of the coated substance on the stent.

46. The stent of claim 39, wherein the tubular structure is balloon
25 expandable.

47. The stent of claim 39, wherein the tubular structure is self-expandable.

48. The stent of claim 39, wherein at least a portion of the tubular

structure is made of a shape memory alloy.

49. The stent of claim 39, wherein the plurality of cavities are substantially evenly positioned on the tubular structure.

50. The stent of claim 39, wherein the plurality of cavities increase a flexibility of the stent without substantially reducing a radial strength of the stent in a deployed state.

51. The stent of claim 39, wherein the plurality of cavities are micro-holes that extend from the outer surface.

52. The stent of claim 51, wherein the micro-holes have a cross-section that is smaller than a cross section of a strut.

53. The stent of claim 39, wherein the plurality of cavities are micro-slits that extend from the outer surface.

54. The stent of claim 55, wherein the micro-slits have a cross-section that is smaller than a cross section of a strut.

55. A stent assembly, comprising:
a balloon; and

an expandable stent positioned at an exterior of the balloon, the stent including,

a tubular structure including an outer surface positionable adjacent to a vessel wall, an inner surface facing a lumen of a body passageway, a plurality of expansion struts, connector struts and cells, the tubular structure having a first diameter which permits intraluminal delivery of the tubular structure into the body passageway having a lumen, and a second expanded and deformed diameter upon the application from the interior of the tubular member of a radially, outwardly extending force applied by the balloon;

a plurality of cavities formed in the outer surface of the stent; and
a coating substance on at least a portion of outer surface of the stent including and extending into at least a portion of the cavities.

56. The stent of claim 55, wherein the coating substance is on at least a portion of the inner surface of the stent.

57. The stent of claim 55, wherein the coating substance is a restenosis inhibiting agent.

5 58. The stent of claim 55, wherein the restenosis inhibiting agent is selected from a drug, polymer and bio-engineered material.

59. The stent of claim 55, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to increase an amount of restenosis inhibiting agent coated on the stent.

10 60. The stent of claim 55, wherein each of a cavity of the plurality of cavities is configured to have a shape adapted to provide a reservoir of the coated substance on the stent.

61. A method of manufacturing an intravascular stent, comprising:
forming an intravascular stent having an inner surface and an outer
15 surface; and
forming a plurality of cavities on the outer surface of the intravascular stent; and
disposing on at least a portion of the outer surface and at least a portion of the plurality of cavities a coating substance that inhibits restenosis.

20 62. The method of claim 61, wherein at least a portion of the plurality of cavities is formed on the outer surface of the intravascular stent by a laser.

63. The method of claim 61, wherein the at least a portion of the plurality of cavities is formed on the outer surface of the intravascular stent by EDM.

25 64. The method of claim 61, wherein the at least a portion of the plurality of cavities is photochemically formed on the outer surface of the intravascular stent.




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D

5/7




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 December 2001 (13.12.2001)


PCT

(10) International Publication Number
WO 01/93781 A3

- (51) International Patent Classification⁷: A61F 2/06
- (21) International Application Number: PCT/US01/18419
- (22) International Filing Date: 5 June 2001 (05.06.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/209,255 5 June 2000 (05.06.2000) US
- (63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 60/209,255 (CIP)
Filed on 5 June 2000 (05.06.2000)
- (71) Applicant and
(72) Inventor: JANG, G., David [US/US]; 30725 Eastern Lane, Redlands, CA 92374 (US).
- (74) Agent: DAVIS, Paul; Wilson Sonsini Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report:
18 April 2002

[Continued on next page]

(54) Title: INTRAVASCULAR STENT WITH INCREASING COATING RETAINING CAPACITY



(57) Abstract: An expandable stent includes a tubular structure with an outer surface positionable adjacent to a vessel wall and an inner surface facing a lumen of a body passageway. The tubular structure further includes a plurality of expansion struts, connector struts and cells. The tubular structure has a first diameter which permits intraluminal delivery of the tubular structure into the body passageway, and a second expanded and deformed diameter which is achieved upon the application of a radially, outwardly extending force. A plurality of cavities are formed in the outer surface of the stent.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 01/18419

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 36784 A (COOK INCORPORATED) 27 August 1998 (1998-08-27)	1-8, 10, 12, 14-17, 19, 21, 26-30, 33-64
Y	page 27, line 17 -page 28, line 8; figures 8-10	9, 11, 18, 20
Y	WO 98 23228 A (ALZA CORPORATION) 4 June 1998 (1998-06-04) page 16, line 19 -page 17, line 2; figure 10	9, 11, 18, 20
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

28 February 2002

Date of mailing of the international search report

06/03/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Smith, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/18419

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Creation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 950 386 A (CORDIS CORPORATION) 20 October 1999 (1999-10-20)	1-5, 16, 17, 19, 21-26, 28-30, 33-39, 41-49, 53-55, 57-62
Y	the whole document	27, 40, 56
Y	WO 99 23977 A (EXPANDABLE GRAFTS PARTNERSHIP) 20 May 1999 (1999-05-20) abstract; figures	27, 40, 56

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/18419

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9836784	A	27-08-1998	AU 737252 B2	16-08-2001
			AU 6663298 A	09-09-1998
			EP 0968013 A1	05-01-2000
			JP 2001512354 T	21-08-2001
			WO 9836784 A1	27-08-1998
WO 9823228	A	04-06-1998	AU 5266698 A	22-06-1998
			WO 9823228 A1	04-06-1998
			US 6071305 A	06-06-2000
			ZA 9710342 A	10-06-1998
EP 950386	A	20-10-1999	US 6273913 B1	14-08-2001
			EP 0950386 A2	20-10-1999
			US 2001029351 A1	11-10-2001
			US 2001027340 A1	04-10-2001
WO 9923977	A	20-05-1999	AU 1451699 A	31-05-1999
			EP 1028672 A1	23-08-2000
			JP 2001522640 T	20-11-2001
			WO 9923977 A1	20-05-1999
			US 6190404 B1	20-02-2001